

PRODUCT INFORMATION SHEET

CARPLAN FIRE PUTTY

DESCRIPTION

Carplan Fire Putty can be used on all exhaust systems, flues and boiler pipes. Fire Putty helps with assembly and sets hard with heat.

ADVANTAGES

- Can be used on all exhaust systems
- Aids joint assembly and sets hard with heat
- Withstands temperatures of up to a 1000℃

PROPERTIES

Annogrange	Dooto
Appearance	Pasie
Color	Grey

DIRECTIONS FOR USE

- Clean surface, pipes and gaskets.
- Apply Fire Putty to all connecting surfaces.
- Tighten all clamps and bolts.

HEALTH AND SAFETY

Irritating to eyes and skin. Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water.

AVAILABILITY

120g – FIP120 500g – FIP500

11/06/09 Page 1 of 2



DISCLAIMER

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED BEVIS GREEN WORKS WALMERSLEY BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

11/06/09 Page 2 of 2



SAFETY DATA SHEET **FIRE PUTTY**

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME FIRE PUTTY

PRODUCT NO. FIP120, FIP500, FEW003

INTERNAL ID

APPLICATION Sealant.

SUPPLIER TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin.

CLASSIFICATION (1999/45) Xi;R36/38.

HUMAN HEALTH

See section 11 for additional information on health hazards.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
SODIUM SILICATE		1344-09-8	10-30%	Xi;R36/38.

The Full Text for all R-Phrases is Displayed in Section 16

The Full Text for all

R-Phrases is Displayed in

Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

NOTES TO THE PHYSICIAN

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

INHALATION

Get medical attention if any discomfort continues.

INGESTION

Consult a physician for specific advice.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

Report Date : 04/01/2012 REVISION DATE 23/09/2009

SDS No. 16039

FIRE PUTTY

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb spillage with non-combustible, absorbent material.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Avoid spilling, skin and eye contact. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep away from food, drink and animal feeding stuffs. Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT





PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

ENGINEERING MEASURES

Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

Goggles/face shield are recommended.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

Report Date: 04/01/2012 REVISION DATE 23/09/2009

FIRE PUTTY

SDS No.

16039

HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Viscous Paste

10 STABILITY AND REACTIVITY

STABILITY

No particular stability concerns.

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

Because of quantity and composition, the health hazard is small.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

LABELLING



Irritant

RISK PHRASES

R36/38 Irritating to eyes and skin.

SAFETY PHRASES

S2 Keep out of the reach of children. S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of

water and seek medical advice.

S37 Wear suitable gloves.

S46 If swallowed, seek medical advice immediately and show this

container or label.

S56 Dispose of this material and its container to hazardous or

special waste collection point.

Report Date: 04/01/2012 4 / 4
REVISION DATE 23/09/2009 SDS No. 16039

FIRE PUTTY

S64

If swallowed, rinse mouth with water (only if the person is conscious).

UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material.

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

ISSUED BY

HS&E Manager. Health & Safety Department REVISION DATE 23/09/2009

REV. NO./REPL. SDS 17

GENERATED

RISK PHRASES IN FULL

R36/38 Irritating to eyes and skin.

DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.